Product data sheet

NADJA VII (1-ARMED) 9.876.2152.85

LEIPZIGER LEUCHTEN









Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp		
Nominal lamp power	50 W	
Lamp flux	3500 lm	
Luminous efficacy	44 lm/W	
CCT	2000 k	
CRI	25	

LOR	78%
Total flux	2737 lm
Total power	62 W



1 x High pressure sodium vapour lamp		
Nominal lamp power	70 W	LC
Lamp flux	5600 lm	To
Luminous efficacy	53 lm/W	To
CCT	2000 K	
CRI	25	

 0 W
 LOR
 78%

 0 Im
 Total flux
 4379 Im

 n/W
 Total power
 83 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 16.54 in Diameter: 16.54 in Electric

System power: 62-83 W

Protection

IP: 55