



Product data sheet

ECLDISPLAYCAS_WHITE
ECLDISPLAYCAS_5600K_WASH 1530DEG_MAX ZOOM
PROLIGHTS



EclDisplay is a range of revolutionary and flexible LED spotlights designed for galleries, retail and any public venue where an advanced but classical looking fixture is needed, with several control options, sources and optic versions available to precisely meet any application. The EclDisplay CAS is the version of the EclDisplay range made with integrated CASAMBI control on-board, leaving to System Integrators to install this luminaire in venues with their own wiring distribution and control. EclDisplay CAS includes a high-efficiency 25W single color LED available in 2700K, 3000K, 4000K and 5600K versions both in black and white finishing, and it is completed with a wide selection of optional zoomable profile or wash lenses, and other optical accessories like louvres and snoots, making it a truly a multi-purpose fixture. Main features: CASAMBI control on-board 25W single color LED available in 2700K, 3000K, 4000K and 5600K versions both in black and white finishing Multiple lens options: zoomable profile or wash optics

Light output 1



1 x LED			
Nominal lamp power	33.7 W	LOR	100%
Lamp flux	1764 lm	Total flux	1768 lm
Luminous efficacy	52 lm/W	Total power	33.7 W
CCT	5641 K		
CRI	91		

Mounting mode

Ceiling mounted, Contact rail, Standing / Bollard

Shape and measurements

Length: 5.55 in
Width: 3.35 in
Height: 7.51 in

Adjustability

Rotatable, Tilttable, Free

Electric

System power: 33.7 W
Controller: DMX, DALI
Color adjustable
Appliance Class: I

Protection

IP: 20
IK: 08
Surface temperature: 65°C
Designation labels: CE