

Product data sheet

LOUI 50
925338.003
RZB




IP
20

IK
03

Series: LESS IS MORE 50;system Gerades Einbaumodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem für Montage in Zwischendecken oder Leichtbau-Hohlwände. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Diffusor(en) aus vergilbungsfreiem Kunststoff (PMMA) opal. Colour: deep black, matt (RAL;9005) Length: 1401;mm Width: 71;mm Height: 1.5;mm Cut-out length: 1408;mm Cut-out width: 60;mm Recess height: 100;mm Luminaire: recess height: 75;mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 34;W Rated luminous flux: 3850;lm Luminous efficiency: 113;lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP;20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	34 W	CRI	80
Total flux	3850 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	34 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.80 in
Width: 55.16 in
Height: 0.08 in

Adjustability

Fixed

Electric

System power: 34 W

Protection

IP: 20
IK: 03