
Product data sheet


SINUS SUSP. DI/ID BLACK PRISM. 2950MM
R33H295-9005E2HCLX3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40


dynamic white LED 2700-6500K CRI 90 437,2W 45002lm¹ DALI DT8 ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 13,1% https://katalog.planlicht.com/en-gb/fam-sinus/

Light output 1 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	54.65 W	CRI	90
Total flux	5625 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	54.65 W

Light output 2 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	54.65 W	CRI	90
Total flux	5625 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	54.65 W

Light output 3 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	54.65 W	CRI	90
Total flux	5625 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	54.65 W

Light output 4 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	54.65 W	CRI	90
Total flux	5625 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	54.65 W

Light output 5 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	54.65 W	CRI	90
Total flux	5625 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	54.65 W

Light output 6 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	54.65 W	CRI	90
Total flux	5625 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	54.65 W

Light output 7 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	54.65 W	CRI	90
Total flux	5625 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	54.65 W

Light output 8 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	54.65 W	CRI	90
Total flux	5625 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	54.65 W

Mounting mode

Pendant

Shape and measurements

Length: 116.14 in
Width: 116.14 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 437.2 W
Color adjustable

Protection

IP: 40