
Product data sheet

KOMBIC 70 SUT 1500 IP20 9WW RF WFL D B/B
K71SF1520RF827DBB
LAMP



LAMP Suspended or ceiling mounting downlight KOMBIC 70 SUT 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in black and Wide Flood reflector for greater efficiency and to achieve controlled light distribution and low glare level, less than UGR<19. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K and IRC90. Electronic DALI gear included. IP20 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. Available finishes: White and black.

Light output 1



1 x LED

Nominal lamp power	10.3 W	LOR	100%
Lamp flux	762 lm	Total flux	761 lm
Luminous efficacy	74 lm/W	Total power	10.3 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant

Shape and measurements

Height: 5.51 in
Diameter: 2.76 in

Adjustability

Fixed

Electric

System power: 10.3 W
Appliance Class: II

Protection

IP: 20