
Product data sheet


PML WITH BRACKET OSLO 650-2 - WITH LOUVRES DOUBLE ASY35 16LED 2200K
88.02400.0V002 + 10.32401.2V001
HESS



IP 54


Round luminaire canopy, horizontally split in two, made of aluminium, plain coloured. Support elements made of aluminium, painted. Cylindrical luminaire enclosure made of PC. Round luminaire body made of aluminium with louvres. 10.32401.2V001 PARALLEL TUBES Bracket OSLO 650/650-2 double Parallel tubes Made of galvanised steel Overhanging 450 mm on each side Spigot pole ø 76,1 mm

Light output 1




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2190 lm	Total flux	2190 lm
Luminous efficacy	108 lm/W	Total power	20.2 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	1926 lm	Total flux	1926 lm
Luminous efficacy	107 lm/W	Total power	18 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1656 lm	Total flux	1656 lm
Luminous efficacy	105 lm/W	Total power	15.7 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1389 lm	Total flux	1389 lm
Luminous efficacy	104 lm/W	Total power	13.4 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1117 lm	Total flux	1117 lm
Luminous efficacy	101 lm/W	Total power	11.1 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	2697 lm	Total flux	2697 lm
Luminous efficacy	109 lm/W	Total power	24.8 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	2942 lm	Total flux	2942 lm
Luminous efficacy	109 lm/W	Total power	27.1 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2446 lm	Total flux	2446 lm
Luminous efficacy	109 lm/W	Total power	22.5 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	3657 lm	Total flux	3657 lm
Luminous efficacy	108 lm/W	Total power	33.9 W
CCT	2200 K		
CRI	80		



1 x LED


Nominal lamp power	31.6 W	LOR	100%
Lamp flux	3423 lm	Total flux	3423 lm
Luminous efficacy	108 lm/W	Total power	31.6 W
CCT	2200 K		
CRI	80		



1 x LED


Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3185 lm	Total flux	3185 lm
Luminous efficacy	108 lm/W	Total power	29.4 W
CCT	2200 K		
CRI	80		

Light output 2




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	1926 lm	Total flux	1926 lm
Luminous efficacy	107 lm/W	Total power	18 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	3657 lm	Total flux	3657 lm
Luminous efficacy	108 lm/W	Total power	33.9 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	3423 lm	Total flux	3423 lm
Luminous efficacy	108 lm/W	Total power	31.6 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3185 lm	Total flux	3185 lm
Luminous efficacy	108 lm/W	Total power	29.4 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	2942 lm	Total flux	2942 lm
Luminous efficacy	109 lm/W	Total power	27.1 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	2697 lm	Total flux	2697 lm
Luminous efficacy	109 lm/W	Total power	24.8 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2190 lm	Total flux	2190 lm
Luminous efficacy	108 lm/W	Total power	20.2 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1656 lm	Total flux	1656 lm
Luminous efficacy	105 lm/W	Total power	15.7 W
CCT	2200 K		
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1389 lm	Total flux	1389 lm
Luminous efficacy	104 lm/W	Total power	13.4 W
CCT	2200 K		
CRI	80		



1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1117 lm	Total flux	1117 lm
Luminous efficacy	101 lm/W	Total power	11.1 W
CCT	2200 K		
CRI	80		



1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2446 lm	Total flux	2446 lm
Luminous efficacy	109 lm/W	Total power	22.5 W
CCT	2200 K		
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 38.43 in
Width: 3.74 in
Height: 12.91 in

Adjustability

Fixed

Electric

System power: 22.2-67.8 W

Protection

IP: 54