Product data sheet


CIRCULAR DOWNWARD 3 RINGS (Ø2000 Ø1200 Ø600)
CS4H-00X9AZDUEF
LEDSC4



IP 20

LedsC4 Circular Downward 3 Rings (ø2000 ø1200 ø600) CS4H-00X9AZDUEFV1 Pendant for indoor use. For downlighting. Structure finish: Gold. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 0 Product width or diameter (mm): 2060 Product height (mm): 6000 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 182.5W. Colour temperature: 4000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 10.8. Photobiological risk: RG1. Real flux (lm): 16263. Real lm/W: 86. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 190. Power factor: 0.90. Dimmable equipment included: DALI/PUSH.


Light output 1



1 x LED

Nominal lamp power	127 W	LOR	100%
Lamp flux	8757 lm	Total flux	8757 lm
Luminous efficacy	69 lm/W	Total power	127 W
CCT	4000 K		
CRI	90		


Light output 2



1 x LED

Nominal lamp power	69.5 W	LOR	100%
Lamp flux	5004 lm	Total flux	5004 lm
Luminous efficacy	72 lm/W	Total power	69.5 W
CCT	4000 K		
CRI	90		

Light output 3



1 x LED

Nominal lamp power	37.5 W	LOR	100%
Lamp flux	2502 lm	Total flux	2502 lm
Luminous efficacy	67 lm/W	Total power	37.5 W
CCT	4000 K		
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 78.74 in
Width: 78.74 in
Height: 1.77 in

Adjustability

Fixed

Electric

System power: 234 W
Appliance Class: I

Protection

IP: 20