


Product data sheet

ELSA-2 DL 225 OP 110° 1800 840 DALI WH
E010298950
ESYLUX



LED downlight, 18 W for ceiling mounting User interface: DALI-Bus Control system: DALI Installation type: Recessed mounting Installation position: Ceiling Dimensions: Height/Depth 25 mm, Ø 240 mm Weight: 1000 g Protection type: IP20 ApplianceClass: Class II Permissible ambient temperature: -20 °C...+40 °C Colour: white, similar to RAL 9003 Nominal voltage: 220 - 240 V AC/DC / 50 - 60 Hz TotalSystemPower: 19 W Luminous flux: 1800 lm Luminous efficacy: 94 lm/W Colour temperature: 4000 K Colour rendering index R_a: > 80 Rated lifetime L₈₀ at 25 °C: 40000 hArticleNumber: E010298950 <https://www.esylux.com/p/E010298950>

Light output 1



1 x LED			
Nominal lamp power	19 W	LOR	100%
Lamp flux	1800 lm	Total flux	1800 lm
Luminous efficacy	95 lm/W	Total power	19 W
CCT	4000 K		
CRI	81		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.98 in
Diameter: 9.45 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 19 W
Ballast: ECG
Controller: DALI
Appliance Class: II

Protection

IP: 20
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...104°F