
Product data sheet

KOMBIC 100 SQ 2500 IP43 840 ELI. D MA/W
K11SQ2543EL840DMW
LAMP



KOMBIC 100 square recessed downlight by LAMP. Reflector made of recycLED polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in matt metallic and frame in white finish. Elliptical optic option is the perfect choice for lighting walkways and longitudinal areas such as counters or areas adjacent to work areas. This product allows for increased spacing between luminaires, reducing the effect of residual light on walls and providing a pleasant atmosphere in the space. Heatsinkmade of die-cast aluminium. COB LED, colour temperature 4000K with CRI80. Luminaire with electronic wiring Dali included. Insulation class II. LED life time: 50000 L80 B10. With IP43 degree of protection. Group 0 photobiological safety.

Light output 1



1 x LED

Nominal lamp power	19.8 W	LOR	100%
Lamp flux	2141 lm	Total flux	2137 lm
Luminous efficacy	108 lm/W	Total power	19.8 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in
Width: 3.94 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 19.8 W
Appliance Class: II

Protection

IP: 43