


Product data sheet

EMERGENCY - MERLIN EMERGENCY DOWNLIGHT - WHITE
AMELED/OA/3NM/ST
ANSELL LIGHTING




AMELED/OA/3NM/ST EMERGENCY Merlin LED Emergency Downlight - White LED 5W Non-Maintained - Open Area - Emergency Supplied c/w Remote Driver and Battery Pack • Ultra-low profile recessed self-test emergency downlight • Self-test as standard • Option of escape route or open area models • High specification optic design and performance allows increased spacing providing reduced cost • Up to 17.8 metres spacing between luminaires Operating Temp 0°C to 40°C • Suitable for both internal and external use • 3 Year Product Warranty • IP20

Light output 1 (emergency)



1 x LED			
Nominal lamp power	5 W	LOR	100%
Lamp flux	274 lm	Total flux	274 lm
Luminous efficacy	55 lm/W	Total power	5 W
CCT	6500 K		
CRI	70		

Light output 2



1 x LED			
Nominal lamp power	0.1 W	LOR	100%
Lamp flux	1 lm	Total flux	1 lm
Luminous efficacy	10 lm/W	Total power	0.1 W
CCT	6500 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 0.04 in
Diameter: 3.35 in

Adjustability

Fixed

Electric

System power: 5.1 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20
Designation labels: CE