


# Product data sheet

FLAT POLYMERO  
312096.002.3  
RZB



IP  
40

IK  
03

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 620, H 160 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 3200lm System power: 33W Beam Angle: 117° Number of fittings B10A: 53 Number of fittings B16A: 85 Number of fittings C10A: 53 Number of fittings C16A: 85 Inrush current: 0,2A Unified Glare Ratio: 18,7 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	33 W	CRI	80
Total flux	3200 lm	LOR	100%
Luminous efficacy	97 lm/W	ULOR	13%
		Total power	33 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 6.30 in  
Diameter: 24.41 in

## Adjustability

Fixed

## Electric

System power: 33 W

## Protection

IP: 40  
IK: 03