Product data sheet


LED DOWNLIGHTS
V1-R0-W0137-20000-5402440 DL-ROLL OPAL Ø140 SURFACE MOUNTED 24W 4000K
VARTON



IP 54 IK 01

Input voltage (AC, 50Hz): 198...264 AC frequency: 50 Flicker: 1 Climatic modification and category of placement: УХЛ4 Protection class: II Housing material: Aluminium Mounting method: Surface mounting Ingress protection (IP): IP54 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/daunlayty/dl-roll/dl-roll-opal-140-nakladnye/svetodiodnyy-svetilnik-varton-dl-roll-nakladnoy-24-vt-4000-k-140kh190-mm-ip54-ral9016-belyy-muar-s-r_1/

Light output 1



1 x LED

Nominal lamp power	24 W	LOR	100%
Lamp flux	2400 lm	Total flux	2400 lm
Luminous efficacy	100 lm/W	Total power	24 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 7.48 in
Diameter: 5.51 in

Adjustability

Fixed

Electric

System power: 24 W

Protection

IP: 54
IK: 01