

Product data sheet


ML56 LED RECESSED DOWNLIGHTS 90 CRI - 5 & 6 INCH
ML5606935-594SNB-30
COOPER LIGHTING



IP
47

ENERGY STAR® Certified. Learn more at energystar.gov, 600 Design Lumens (typical), 90 CRI, Available in 2700K, 3000K, 3500K and 4000K color temperatures, D2W option - LED warms from 3000K to 1850K, Retrofits existing 5" or 6" housings with screwbase adapter included, Use with Halo 5" & 6" LED new construction & remodel housings, 120V-277V UNV Integral, thermally protected electronic LED driver, Dimmable on 120V phase-control dimmers, Wet location shower listed with reflector and baffle trims, ML56 modules with downlight trims make housings AIR-TITE™ (ASTM E283)

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9.59 W	CRI	100
Total flux	757 lm	LOR	100%
Luminous efficacy	79 lm/W	ULOR	2%
		Total power	9.59 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in
Width: 3.94 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 9.59 W

Protection

IP: 47