# Product data sheet


NUMINOS® CL, DALI
1004583
SLV



IP 00

NUMINOS® is the perfect flexible and modular lighting system from SLV. It combines a variety of sizes and functions with a modern design and high efficiency (more than 120lm/W). NUMINOS® offers more than a thousand design options with downlights and spotlights. The NUMINOS® CL, DALI LED lights offer high-quality workmanship and ensure excellent illumination of small and large areas. The Deckenaufbauleuchte The luminaire impresses with a luminous flux of 2300 lm and an impressive efficiency of 121.05 lm/W. Their colour temperature of 2700 Kelvin and their colour rendering index > 90 fit perfectly into your project. In combination with the simple installation, NUMINOS® is the perfect solution for a wide range of applications and projects.

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 2687 K |
| Nominal lamp power | 28.1 W | CRI | 90 |
| Total flux | 2402 lm | LOR | 100% |
| Luminous efficacy | 85 lm/W | Total power | 28.1 W |

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 42.13 in
Width: 7.09 in
Height: 3.94 in
Weight: 1.07 kg

### Adjustability

Tiltable

### Electric

System power: 28.1 W
Controller: DALI
Appliance Class: II

### Protection

IP: 00