
Product data sheet

NADJA III (WALL FITTING BEADED) 9.846.3162.06



Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp				
Nominal lamp power	125 W	LOR		
Lamp flux	6800 lm	Total flux		
Luminous efficacy	39 lm/W	Total power		

125 W	LOR	78%
6800 lm	Total flux	5302 lm
39 lm/W	Total power	137 W
3400 K		
54		

1148-444	1
	-
	5
	\leq
XHX	
XTE	X

1 x High pressure mercury vapour lamp					
Nominal lamp power	80 W	LOR	78%		
Lamp flux	4000 lm	Total flux	3119 lm		
Luminous efficacy	35 lm/W	Total power	89 W		
CCT	3400 K				
CRI	54				

Mounting mode	Electric
Wall mounted	System power: 89-137 W
Shape and measurements	Protection
Height: 16.54 in	IP: 55
Diameter: 16 E4 in	

CCT CRI

9 ŀ

Diameter: 16.54 in