


Product data sheet

X-LINE SLIM RECESSED LOW UGR LED 4200 RASTER DAISY-BLACK-WIDE EDD 24 840 LINE-1EP / L-1133MM
19.4158.2323.24
LUXIONA



Indoor luminaire. Assembly: mounted in plasterboard ceilings. The body material is aluminum. Colour - anodised aluminum. Dimensions: 1133 x 70 x 75 mm. Mounting hole: 1128 x 55 mm. Diffuser: RASTER (anti-glare louver). The efficiency of the optical system is 82,98%. Beam angle: (C0-C180) / (C90-C270) - 72,6° / 74,4°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 3678,6 lm. Power of luminaire: 25,5 W. Luminaire's light efficiency: 144,3 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 17 (B10), 28 (B16), 26 (C10), 41 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. The luminaire can be made in CLO (Constant Lumen Output) version. *Selected luminary variants are available with ENEC certificate.

Light output 1



1 x LED			
Nominal lamp power	25.5 W	LOR	52%
Lamp flux	4432 lm	Total flux	2324 lm
Luminous efficacy	174 lm/W	Total power	25.5 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 44.96 in

Width: 2.76 in

Height: 2.95 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 25.5 W

Controller: DALI

Appliance Class: I

Protection

IP: 40

IK: 04

Other operating numbers

Ambient temperature range: 41...95°F