


Product data sheet

3604.1 LED CG-S WHITE


40071352909

EATON EMERGENCY LIGHTING




• Safety luminaire with LED technology for recessed mounting with square bezel • Typical ceiling cut-out diameter of 68 mm and low profile of only 30 mm • Compact housing for LED supply (required height for entering the ceiling only 100 mm) including through-wiring clamp and strain relief • Wide light point spacing due to wide light distribution optics and high power LEDs • Up to 18 m from luminaire to luminaire for escape route illumination and wide area illumination (3x03.1) • Up to 20 m from luminaire to luminaire for escape route illumination and wide area illumination (3x04.1)

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.4 W	CRI	80
Total flux	620 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	4.4 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.4 W	CRI	80
Total flux	620 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	4.4 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.15 in

Width: 3.15 in

Height: 0.08 in

Adjustability

Fixed

Electric

System power: 8.8 W

Appliance Class: II

Information regarding emergency functions

Supplementary emergency lighting

Emergency power supply: Central battery feed-in

Emergency sign: N/A

Protection

IP: 20

IK: 03