Product data sheet


LUMINAIRE OSLO 650-2 - WITHOUT LOUVERS M5 16LED 2700K
88.02400.0V001
HESS



IP 54


Round luminaire canopy, horizontally split in two, made of aluminium, plain coloured. Support elements made of aluminium, painted. Cylindrical luminaire enclosure made of PC. Round luminaire body made of aluminium without louvres.

Light output 1




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1966 lm	Total flux	1966 lm
Luminous efficacy	125 lm/W	Total power	15.7 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1649 lm	Total flux	1649 lm
Luminous efficacy	123 lm/W	Total power	13.4 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1325 lm	Total flux	1325 lm
Luminous efficacy	119 lm/W	Total power	11.1 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2600 lm	Total flux	2600 lm
Luminous efficacy	129 lm/W	Total power	20.2 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2904 lm	Total flux	2904 lm
Luminous efficacy	129 lm/W	Total power	22.5 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	2286 lm	Total flux	2286 lm
Luminous efficacy	127 lm/W	Total power	18 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	4341 lm	Total flux	4341 lm
Luminous efficacy	128 lm/W	Total power	33.9 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	4063 lm	Total flux	4063 lm
Luminous efficacy	129 lm/W	Total power	31.6 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3781 lm	Total flux	3781 lm
Luminous efficacy	129 lm/W	Total power	29.4 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	3493 lm	Total flux	3493 lm
Luminous efficacy	129 lm/W	Total power	27.1 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	3202 lm	Total flux	3202 lm
Luminous efficacy	129 lm/W	Total power	24.8 W
CCT	2700 K		
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 25.58 in
Width: 25.58 in
Height: 19.33 in

Adjustability

Fixed

Electric

System power: 11.1-33.9 W

Protection

IP: 54