Product data sheet

LUCAS II (WALL FITTING) 9.836.2056.15

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp	
Nominal lamp power	100 W
Lamp flux	10400 lm
Luminous efficacy	76 lm/W
CCT	2000 H
CRI	25

LOR 84%
Total flux 8713 lm
Total power 115 W



i x i ligii pressure soulurii	vapoui iaiTip
Nominal lamp power	70 W
Lamp flux	5600 lm
Luminous efficacy	57 lm/W

1 v High pressure codium vanour lamp

CCT 2000 K
CRI 25

LOR 84%
Total flux 4691 lm
Total power 83 W

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in Electric

System power: 83-115 W

Protection

IP: 55