Product data sheet

PLANOX
672200.009.89
RZB



IP 66 IK 03

Item Number: 672200.009.89 Series: Planox Type of Protection: IP 66 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: plastic polycarbonate, prepared for two suspension chains or cables (suspension provided on site), interior fastening element made of sheet steel, painted white, converter integrated, refractor plastic (PMMA), opal prismatic inside, refractor attached using retaining clips made of stainless steel, with AC Control monitoring module for Luxifair central battery units. LED included. Available Colours: light grey (RAL 7035) Type of Installation: Ceiling mounting, Suspension cable/chain, Wall (surface) Dimensions: L 1278, B 96, H 100mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Emergency Lighting System: AC-Control Safety Marks: D-mark, F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 5700lm System power: 49W Beam Angle: 131°/95° Unified Glare Ratio: 25,0 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	52 W	CRI	80
Total flux	5700 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	7%
		Total power	52 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.78 in
Width: 50.31 in
Height: 3.94 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 52 W

Protection

IP: 66
IK: 03