

Product data sheet


SPOT REVO MULTIMETRIK 48 TW COMPACT 1XTRACK48 LED 20.9W RA92 2700K 48V/DC IP40 MULTIMETRIK WIDE FLOO
387-T1-_-_-2T-MA.WF CLOSED TW@2700K
EXENIA



IP
40

Multimetrik integrates REVO optical technology, offering an adjustment system that allows the light emission to be adapted to application needs. The light beam is adjustable within a range of 15° to 60° thanks to the micro-translation of the focal point, ensuring precision and uniformity. The light intensity can be adjusted via an onboard dimmer. The luminous efficiency reaches 132 lm/W with fluxes up to 3500 lm, maintaining a high-quality standard. The compact design allows integration into Exenia products without altering their aesthetics, ensuring visual continuity with fixed beam versions. Interchangeable lenses provide precise and uniform beams, making Multimetrik a versatile solution for various applications. Available in Medium, Compact, and Max variants, with dynamic white (2700K-4000K) or fixed color temperatures (2700K, 3000K, 3500K, 4000K) with a CRI of up to 98 and a chromatic tolerance of up to 2 MacAdam Steps.

Light output 1



1 x LED			
Nominal lamp power	23.4 W	LOR	100%
Lamp flux	1770 lm	Total flux	1762 lm
Luminous efficacy	76 lm/W	Total power	23.4 W
CCT	2700 K		
CRI	92		

Mounting mode

Ceiling mounted

Electric

System power: 23.4 W

Shape and measurements

Length: 2.95 in
Width: 2.95 in
Height: 4.25 in

Protection

IP: 40

Adjustability

Fixed