
Product data sheet

M26L - SPY 392 92720 DIM5
23261 9225
DELTA LIGHT




Luminaire, low voltage systems low voltage system mounted (indoor use) from Deltalight, named M26L - SPY 392 92720 DIM5, available in the colour(s): black, white. This luminaire can be used with the following 48V magnetic lighting system(s): SHIFTLINE M26L - PROFILE. This luminaire is equipped with 2 x (LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm) with build-in converter to operate on a voltage of 48V-DC. Dimming protocol: DALI. Light distributor: reflector 20°.

Light output 1




1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	1041 lm	Total flux	757 lm
Luminous efficacy	116 lm/W	Total power	20 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	1041 lm	Total flux	757 lm
Luminous efficacy	116 lm/W	Total power	20 W
CCT	2700 K		
CRI	90		



1 x LED


Nominal lamp power	9 W	LOR	73%
Lamp flux	1041 lm	Total flux	757 lm
Luminous efficacy	116 lm/W	Total power	20 W
CCT	2700 K		
CRI	90		



1 x LED


Nominal lamp power	9 W	LOR	73%
Lamp flux	1041 lm	Total flux	757 lm
Luminous efficacy	116 lm/W	Total power	20 W
CCT	2700 K		
CRI	90		

Light output 2




1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	1041 lm	Total flux	757 lm
Luminous efficacy	116 lm/W	Total power	20 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	1041 lm	Total flux	757 lm
Luminous efficacy	116 lm/W	Total power	20 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	1041 lm	Total flux	757 lm
Luminous efficacy	116 lm/W	Total power	20 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	9 W	LOR	73%
Lamp flux	1041 lm	Total flux	757 lm
Luminous efficacy	116 lm/W	Total power	20 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

Electric

System power: 40 W

Appliance Class: II

Shape and measurements

Length: 0.79 in

Width: 6.69 in

Height: 0.04 in

Protection

IP: 20

Designation labels: CE