


# Product data sheet

R40  
40120.002.1  
RZB



IP  
40

IK  
02

Series: R40 Type of Protection: IP 40 Protection Class: I Voltage: - 250 / 0 - 60 Hz Base and end caps: plastic. Cover: opal glass, silk finish.  
Available Colours: white Type of Installation: Wall (surface) Dimensions: L 315, B 55, H 80 Lamp: 2 x E14 max. 40 W Socket 1: E14 Operating  
Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Beam Angle: 180°/111° Unified Glare Ratio:  
23,4 EEC: A+ - E

## Light output 1



### 2 x Compact fluorescent lamp

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 7 W     | Socket      | E14    |
| Lamp flux          | 286 lm  | LOR         | 81%    |
| Luminous efficacy  | 33 lm/W | ULOR        | 20%    |
| CCT                | 2700 K  | Total flux  | 465 lm |
| CRI                | 80      | Total power | 14 W   |

## Mounting mode

Wall mounted

## Shape and measurements

Length: 2.17 in  
Width: 12.40 in  
Height: 4.61 in

## Adjustability

Fixed

## Electric

System power: 14 W

## Protection

IP: 40  
IK: 02