



# Product data sheet

AMP L 4600-840 PC WB MWCF  
42929226  
ZUMTOBEL



LED Moisture-proof diffuser luminaire with IP66 protection rating and drip-edge effect for minimising dirt and collection of dust for maximum hygienic requirements. Total power: 32.6 W, Slave luminaire for DALI control (DALI only) with LED converter; patented InvisiClick for clipless mounting and opening of the cover. Cover and basic diffuser made of impact-resistant polycarbonate, temperature- and UV-resistant, made as a single injection-moulded piece. LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 4640 lm, Luminaire efficacy: 142 lm/W. Colour rendering Ra > 80, colour temperature 4000 K. Luminaire with symmetric wide light distribution (wide beam). Mounting via V2A standard spring clips to ceilings, walls or trunking; Integral presence detector for dimming control (corridor function). 5-pole connector terminal. Suitable for through-wiring with H05VV or NYM cable (10A). ambient temperature: -25°C to +50°C. Approved for indoor use with vertical or horizontal wall mounting (see installation instructions). Luminaire wired with halogen-free leads and contains no silicone. Complies with International Food Standard specifications. Designed for BESA box. Class of protection: SC1, 850°C glow-wire tested, Impact strength: IK08, Dimensions: 1600 x 90 x 92 mm; weight: 3.4 kg.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	32.6 W	CRI	80
Total flux	4640 lm	LOR	100%
Luminous efficacy	142 lm/W	ULOR	17%
		Total power	32.6 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 62.99 in  
Width: 3.54 in  
Height: 3.62 in  
Weight: 3.4 kg

## Design

Material impression: Plastic

## Electric

System power: 32.6 W  
Voltage: 220-240 V AC  
Controller: DALI  
Appliance Class: I

## Protection

IP: 66  
IK: 08  
Designation labels: CE