

# Product data sheet


KORA V (1-ARMED)  
9.107.5367.05  
LEIPZIGER LEUCHTEN



IP  
55

One or double-bracket pole luminaire with intensive brightness (height 4.50 and 6.00 m) in order to illuminate streets and footpaths. - Attachment made of plexiglass XT, sandblasted on one side - Computer-optimized reflector systems for high-pressure lamps with clear glass tubular bulbs/DULUX lamps ensures excellent illumination - Special steel luminaire body and unit carrier, available painted in any RAL or DB colour without surcharge, or ground and passivated - Luminaire case fold out for lamp change - Adapter jack connection - Included pole door to take in a cable joint box - Scope of supply includes square pole, incl. special steel bracket and electrical supply element (intermediate unit, ignition unit, condenser) - Available for 3 fastening variants in the ground: flange sheet, flange sheet in order to pave over, or end piece, situated at the pole, to set in the ground Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 2 x Compact fluorescent lamp

Nominal lamp power	36 W	LOR	44%
Lamp flux	2900 lm	ULOR	2%
Luminous efficacy	33 lm/W	Total flux	2566 lm
CCT	2899 K	Total power	78 W
CRI	90		

## Mounting mode

Pole integrated

## Electric

System power: 78 W

## Shape and measurements

Length: 31.50 in

Width: 9.84 in

Height: 3.15 in

## Protection

IP: 55