



Product data sheet

X-LINE SLIGHT UP&DOWN LED 1100/2200 PLX-T/PLX EDD 04 830 LINE-1BM / L-570MM S-1,5M
19.4303.5213.04
LUXIONA



Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9005 (black). Luminaire dimensions: 570 x 34 x 68 mm. Diffuser: PLX-T/PLX (transparent PMMA/PMMA opal) [up/down]. The efficiency of the optical system is 75,53%. Beam angle: (C0-C180) / (C90-C270) - 99,6° / 103°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 2518,4 lm. Power of luminaire: 19,4 W. Luminaire's light efficiency: 129,8 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 17 (B10), 28 (B16), 26 (C10), 41 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED			
Nominal lamp power	19.4 W	LOR	83%
Lamp flux	3340 lm	Total flux	2788 lm
Luminous efficacy	172 lm/W	Total power	19.4 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 22.44 in

Width: 1.34 in

Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 19.4 W

Controller: DALI

Appliance Class: I

Protection

IP: 40

IK: 04

Other operating numbers

Ambient temperature range: 41...95°F