

Product data sheet

BEAMTECH LARGE 2X500LM 1H (DATA FOR ONE LAMP HEAD ONLY)

BT2LL-F1


EATON EMERGENCY LIGHTING



IP 65
IK 07


- High flux luminaire with configuration of two directional LED lamp heads
- Installation up to 25m (30m) with optimum spacing of 36.8m (43.1m) for 1lux (0.5lux) illumination
- E-focus programming. Narrow and Wide light distribution, programmed by the user
- One product applicable for Escape Route or Open area illumination
- User / installer to define light distribution to fit the application
- Suitable for use in large open areas (supermarkets, warehouses, cinemas, theatres, factories, shopping malls, industrial units, stadiums etc.)
- New modern and flexible / modular design, wall or ceiling mounted
- Mains & communication cabling option from all housing sides (back & side entry)
- Locking mechanism of light head preventing accidental change of light heads configuration

Light output 1 (emergency)



1 x LED

Nominal lamp power	4.5 W	LOR	100%
Lamp flux	500 lm	Total flux	500 lm
Luminous efficacy	111 lm/W	Total power	4.5 W
CCT	6500 K		
CRI	80		



1 x LED

Nominal lamp power	4.5 W	LOR	100%
Lamp flux	500 lm	Total flux	501 lm
Luminous efficacy	111 lm/W	Total power	4.5 W
CCT	6500 K		
CRI	80		

Mounting mode

Wall mounted, Ceiling mounted

Shape and measurements

Height: 0.39 in

Diameter: 4.69 in

Adjustability

Fixed

Electric

System power: 4.5 W

Appliance Class: II

Information regarding emergency functions

Emergency lighting only

Emergency power supply: Single battery 1 h, Single battery 3 h

Emergency sign: N/A

Protection

IP: 65

IK: 07