



Product data sheet

RECESSED DIRECTIONAL SPOTLIGHT NOVO 2 ROUND INNER RING FLUSH-MOUNTED ROUND 6.1W 700LM CRI > 90 4000..
2010.9306 - NOV02 RS FM CR68 LED700-940-R35 WH ONF
REGENT



Recessed directional spotlight Novo 2 Round inner ring flush-mounted, with LED, system power: 6.1 W, luminous flux of luminaire 700 lm, colour rendering index CRI > 90, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L90 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, rated current: 47 mA, direct light emission, housing in die-cast aluminium, with ceiling trim, white, RAL 9016, with reflector, 35, 1 integral control gear, ON/OFF, high-quality die-cast aluminium housing, reduced installation time thanks to fully pre-assembled luminaire, including connection to control gear, with through-wiring option, suitable for ceiling thicknesses from 1 to 45 mm protection class II, ingress protection IP20 / IP44, glow wire test 850 °C, impact strength: IK 07 this product contains a light source of energy efficiency class D and EPREL registration number: 2018957 Ø = 85 mm, ceiling cutout ø 68 mm up to 80 mm, ET = 76 mm, swivelling 15°

Light output 1



1 x LED			
Nominal lamp power	9.2 W	LOR	100%
Lamp flux	700 lm	Total flux	700 lm
Luminous efficacy	76 lm/W	Total power	6.1 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 0.04 in
Width: 0.04 in
Height: 0.04 in
Weight: 0.819 kg

Adjustability

Rotatable, Tilttable

Design

Color of housing: White

Electric

System power: 6.1 W
Appliance Class: II

Protection

IP: 44
IK: 07