



Product data sheet

R-LINE LED COMPACT 16000 OPTICS-D-ASY E 34 840 / L-3360MM
19.4450.3521.34
LUXIONA



Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9016 (white). Dimensions: 3360 x 56 x 48 mm. Diffuser: optical system based on PMMA lenses. The efficiency of the optical system is 86,50%. Beam angle: 125°+100°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 14208 lm. Power of luminaire: 97,7 W. Luminaire's light efficiency: 145,4 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 7 (B10), 12 (B16), 12 (C10), 19 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP20. Impact resistant: IK06. Protection against electric shock: II. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED			
Nominal lamp power	97.7 W	LOR	52%
Lamp flux	16426 lm	Total flux	8613 lm
Luminous efficacy	168 lm/W	Total power	97.7 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 132.28 in
Width: 2.20 in
Height: 1.89 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 97.7 W
Appliance Class: II

Protection

IP: 20
IK: 06

Other operating numbers

Ambient temperature range: 41...95°F