



Product data sheet

P.THIRTY SUSP. L-SEG.HOR. SILVER DI/ID OBD
P30-HLFH9006C2940H1Z
PLANLICHT




LED HO 4000K 24,8W 2760lm CRI90 <https://katalog.planlicht.com/en-gb/search?q=p.thirty&type=1-profile-segment>

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.54 W	CRI	90
Total flux	394 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	3.54 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.54 W	CRI	90
Total flux	394 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	3.54 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.54 W	CRI	90
Total flux	394 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	3.54 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.54 W	CRI	90
Total flux	394 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	3.54 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	3.54 W	CRI	90
Total flux	394 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	3.54 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.54 W	CRI	90
Total flux	394 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	3.54 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3.54 W	CRI	90
Total flux	394 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	3.54 W

Mounting mode

Pendant

Electric

System power: 24.8 W

Shape and measurements

Length: 11.57 in

Width: 25.31 in

Height: 1.38 in

Protection

IP: 20

Designation labels: CE

Adjustability

Fixed