


Product data sheet

1710 CRIPTO COB SMALL - WIDE BEAM 4000K CRI 80 43W CLD ANTHRACITE
413056-00
DISANO



Housing: in die-cast aluminium, with cooling fins. Optics: in high-performance prismatic and polished aluminium. Diffuser: tempered glass, 4 mm thick, resistant to thermal shock and impact (UNI EN 12150-1:2001). Coating: the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint. Special coating: Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea. Heat Sink: the heat sink is designed and made to allow the LEDs to operate at temperatures capable of ensuring excellent performance/output and long service life. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: - with galvanised and painted bracket - cable for electrical connection - EN 61547 compliant surge protection - silicone rubber gasket - external screws and bolts in stainless steel. On request: - protection of up to 10kV - AMBER LED 2200K subcode -73 - CLD-D (1-10V) wiring, subcode -12 - CLD-D-D (DALI) wiring, subcode -0041 - possibility of central light management or with external presence/light sensors.

Light output 1



1 x LED			
Nominal lamp power	43 W	LOR	100%
Lamp flux	5257 lm	Total flux	5257 lm
Luminous efficacy	122 lm/W	Total power	43 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 13.19 in
Width: 9.17 in
Height: 2.36 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Anthracite / graphite

Electric

System power: 43 W
Appliance Class: II

Protection

IP: 66
IK: 09
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -4...104°F