


Product data sheet

APOLLO G2 1560MM PO 2X92W 090° 30000LM
94305D5W
PRACHT



Food-certified Reflector luminaire APOLLO G2 1560mm PO 2x92W 090° 30000lm 4.000K, class II, with TW 3x1,5mm². New generation of the APOLLO damp-proof reflector luminaire. Swiveling reflectors. Acid and alkali resistant. IP65 protection class. Ideal for industry and logistics. 5-year warranty. Item number: 94305d5w GTIN: 4018098472261 Technical details/specification: Cover made of PO; Housing made of GRP polyester White RAL 9010; 220–240 V 0/50/60 Hz; Energy efficiency class B; Number of light sources / LED rows: 2; IP65; Through-wiring in mm²: 3x1,5; Dimensions: LxWxH: 1560mm x 232mm x 142mm; Diameter: mm

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	184 W	CRI	80
Total flux	30000 lm	LOR	100%
Luminous efficacy	163 lm/W	Total power	184 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 61.42 in
Width: 9.13 in
Height: 5.59 in
Weight: 4.7 kg

Adjustability

Tiltable

Design

Color of housing: White

Electric

System power: 184 W
Appliance Class: II

Protection

IP: 65
IK: 08

Other operating numbers

Ambient temperature range: -4...95°F