


Product data sheet

ROUNDED MIDI
582055.0031
RZB



Series: Rounded Midi Type of Protection: IP 66 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing made of corrosion-resistant pressure die-cast Aluminium for outdoor use, powder coated. Grill with opal glass spherical cap diffuser retained in cover. Screwless cover fixing via bayonet lock with safety catch. Base fixing slots outside of gasketed volume, drill hole deviations can be compensated. Standard with mains voltage LED module. Mains connection 2x 3x 1,5 mm². Available Colours: anthracite metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 268, H 100 Lamp: LED Life time: 50000 h (L70/B50) Colour Temperature: 3000K Socket 1: Stecker Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK08 (5 Joule) Luminaire flux LED: 580lm System power: 13W Beam Angle: 112° Number of fittings B10A: 114 Number of fittings B16A: 182 Number of fittings C10A: 114 Number of fittings C16A: 182 Unified Glare Ratio: 21,0 EEC: A+ - A+A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13 W	CRI	80
Total flux	580 lm	LOR	100%
Luminous efficacy	45 lm/W	ULOR	4%
		Total power	13 W

Mounting mode

Wall mounted

Shape and measurements

Height: 3.94 in
Diameter: 10.55 in

Adjustability

Fixed

Electric

System power: 13 W

Protection

IP: 66
IK: 08