Product data sheet


ASL MIDI DC 12W 830 36D D1 300 CE
DL26PLN102875
TRAXON



IP 65

Easy installation and maintenance DMX Control Auto-addressing IP66 Outdoor Color Options Neutral White (4000K), Warm White (3000K), RGB, RGBW (W:4000K) Easy Fit In Different Architectural Structures Compact size (POWER / MAXI) Slim size (MIDI / MINI) Dedicated Optic Design Even washing effect Optimized color mixing (POWER / MAXI / MIDI) Beam Angles POWER: White – 11°, 36°, 15° × 30° RGB – 36°, 15° × 55° RGBW – 36°, 15° × 55° MAXI: White – 11°, 25°, 36°, 15° × 30°, 15° × 55° RGB – 36°, 15° × 55° RGBW – 11°, 36°, 15° × 55° MIDI: White – 11°, 15° × 30°, 15° × 55°, 25°, 36° RGB – 36°, 10° × 55° RGBW – 20° × 30°, 25° × 50° MINI: White – 20° × 55°, 110° Certifications & Approbations *Please Note: This product is now on phase out. View our new product – Linear Go Can't find what you are looking for? Contact us now Do you need a custom product? Inquire about custom options Looking for control options? Learn more about e:cue controls

Light output 1



1 x LED

Nominal lamp power	12 W	LOR	100%
Lamp flux	855 lm	Total flux	855 lm
Luminous efficacy	71 lm/W	Total power	12 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 11.57 in
Width: 1.14 in
Height: 3.94 in

Adjustability

Rotatable, Tiltable

Electric

System power: 12 W

Protection

IP: 65