



Product data sheet

BERYL PROOF WALL K LED UP&DOWN 2X2000 WIDE E IP65 21 830
19.3140.0015.21
LUXIONA



Outdoor luminaire. Assembly: mounted on wall. The body material is aluminum. Colour - RAL 9006 (grey, metallic, fine structure). Dimensions: 210 x 120 x 370 mm. Weight 3,58 kg. Diffuser: transparent polycarbonate. The efficiency of the optical system is 87,27%. Beam angle: (C0-C180) / (C90-C270) - 93,8° / 89,6°. Light source type: LED. Colour of the light 3000 K. SDCM=2. CRI85. Lifetime of LED sources: 95000 (1) / 100000 (2) / 100000 (3) h L90/B10 (1) / L80/B10 (2) / L70/B10 (3). Luminaire luminous flux: 3840 lm. Power of luminaire: 25,2 W. Luminaire's light efficiency: 152,4 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 20 (B10), 30 (B16), 33 (C10), 53 (C16). Operating temperature range: -25 ÷ 30° C. Protection degree: IP65. Impact resistant: IK06. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG1. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



2 x LED			
Nominal lamp power	12.6 W	LOR	52%
Lamp flux	2200 lm	Total flux	2307 lm
Luminous efficacy	175 lm/W	Total power	25.2 W
CCT	3000 K		
CRI	85		

Mounting mode

Wall mounted

Shape and measurements

Length: 8.27 in
Width: 4.72 in
Height: 14.57 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 25.2 W
Appliance Class: I

Protection

IP: 65
IK: 06

Other operating numbers

Ambient temperature range: -13...86°F