Product data sheet

TOWNGUIDE PERFORMER BDP100 PCF 1 XLED70/830 DS
BDP100
PHILIPS

Philips TownGuide Performer – flexible, modern designs for every application need The TownGuide Performer family consists of six recognizable, yet modern shapes: Flat Cone, Bowl, Classic Cone, Classic T, T and Tzero. Each luminaire has the option of a clear (PCC), translucent (PCTR) or frosted (PCF) bowl (except Tzero, which is only available with a clear bowl). With an extensive range of lumen packages, neutral white or warm white LED lights sources, and a range of dedicated optics for lower mounting heights, it's easy to select the version that best suits the specific requirements of your project. All this combined with a long life expectancy of 100,000 operating hours. In addition, TownGuide Performer has a variety of control system options that can make this luminaire an integral part of smart energy-reduction programs. This includes LumiStep, DynaDimmer, and LineSwitch stand-alone dim control, and Coded Mains group control, right up to seamless remote connectivity with Interact lighting management software. Installation is easy. Thanks to the bayonet whistle connector with integrated gland located in the spigot, there's no need to open the luminaire for installation. The Signify Service tag app offers direct access to all relevant data, ensuring maintenance is easy too. Philips has made every effort to make the Total Cost of Ownership (TCO) of the luminaire as attractive as possible. And as TownGuide Performer is a dedicated LED luminaire, compatible with a variety of control systems, there are significant energy and maintenance cost savings compared with conventional lighting.

Light output 1



1 x LED

Nominal lamp power	56 W	LOR	61%
Lamp flux	7000 lm	ULOR	8%
Luminous efficacy	77 lm/W	Total flux	4286 lm
CCT	3000 K	Total power	56 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 8.23 in

Diameter: 22.44 in

Electric

System power: 56 W