


# Product data sheet

O65-350 LED 120 OP  
GLAMOX



Light source LED 120-1200 830/840 Body material & colour The body is made of extruded clear or opal UV-resistant polycarbonate. End caps in anodized aluminium and fixed end brackets in polycarbonate. Mounting Installation directly on the ceiling or wall with integrated fixed end brackets. Accessories 24Vdc remote power supply. Supply cable with single connector. Supply cable with double connector for row mounting. IP68 terminal blocks. Connection Integrated quick connectors in the end caps. Installation requires connection cables for power supply and row mounting. Maximum total length for row mounting exclusive cables is 5 meters. Cables must be ordered separately. Optics Diffuse (OP). Clear (CL). Power supply 24Vdc remote power supply for fixed output or dimming (1-10V/SwitchDim). Power supply must be ordered separately.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	118 lm	LOR	100%
Luminous efficacy	39 lm/W	ULOR	50%
		Total power	3 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 0.98 in

Diameter: 13.94 in

## Adjustability

Fixed

## Electric

System power: 3 W

Appliance Class: III

## Protection

IP: 65

IK: 06