Product data sheet


STELLA P IV/13 DA LED (OPTIC 028)
6.628.8112.6513028-3AL
LEIPZIGER LEUCHTEN



IP 65

• STELLA P IV: cap made of aluminium and tube made of hot-dip galvanised steel; powder coated • STELLA P I, I/13, IV/13; XXIII, XXIII/13:cap and tube made of aluminium; powder coated • glazing made of PMMA RESIST, clear, high-impact resistant • incl. cable junction box: incl. cable until the cable junction box for max. 2 cables up to 5x16mm²/ 3 cables up to 5x10mm² • with flange plate to be ordered separately: bolt-on root (G240/500 for ø 170mm; G300/500 for ø 200mm; G330/500 for ø230mm) with screws, accessory ring (Z248/1 for ø 170mm; Z305/2 for ø 200mm; Z338 for ø 230mm), back light shield for no glare on the rear side

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12 W	CRI	70
Total flux	1456 lm	LOR	100%
Luminous efficacy	121 lm/W	ULOR	41%
		Total power	12 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 51.18 in
Diameter: 6.69 in
Weight: 13.5 kg

Adjustability

Fixed

Electric

System power: 12 W

Protection

IP: 65