



Product data sheet

1796 FARO 5 LED - SMALL 4000K CRI 80 5W CLD GRAPHITE
510620-00
DISANO



Housing: in extruded aluminium, with cylindrical cross-section with a diam. of 180 mm. Base: in die-cast aluminium. Diffuser: in polycarbonate, transparent, anti-glare, shatterproof and V2 self-extinguishing, UV stabilised. Coating: the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint. Special coating: Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: - with air circulation valve. - complete with waterproof connector for line connection.

Light output 1



1 x LED			
Nominal lamp power	5 W	LOR	100%
Lamp flux	750 lm	Total flux	750 lm
Luminous efficacy	150 lm/W	Total power	5 W
CCT	4000 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 7.20 in

Width: 7.20 in

Height: 13.58 in

Adjustability

Fixed

Design

Material impression: Aluminum

Color of housing: Anthracite / graphite

Electric

System power: 5 W

Appliance Class: II

Protection

IP: 65

IK: 10

Designation labels: CE