Product data sheet


OPUCL L44 W LE3
OPUS COLUMN EMERGENCY
DEXTRA



IP 65


Opus Column - IP65 Column top mounted wide lensed luminaire, matt grey weather resistant and salt spray tested paint finish. Aluminium housing and polycarbonate front cover. Integral column spigot fixing mechanism included and supplied with 10m prewired flex to facilitate installation. Options: LE3 - Lithium Emergency (1049 lumens output) LS3 - Lithium Selftest LA3 - Lithium Autotest PH - Photocell NEM - NEMA Socket S40 - 40-50mm Spigot S50 - 50-60mm Spigot S60 - 60-76mm Spigot OPUC WB - Opus Column Wall Mount Bracket BL - Black Body C73 - CRI 70 3000K

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	70
Total flux	1049 lm	LOR	100%
Luminous efficacy	350 lm/W	ULOR	5%
		Total power	3 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	25.1 W	CRI	70
Total flux	3934 lm	LOR	100%
Luminous efficacy	157 lm/W	ULOR	5%
		Total power	25.1 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 29.02 in
Width: 12.05 in
Height: 4.06 in

Adjustability

Fixed

Electric

System power: 28.1 W
Ballast: ECG

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 65

Designation labels: CE