
Product data sheet


FLUMO60-S 228S-5C1I-120GE/830, W
228S-5C1I-120GE/830
HALLA



IP 20 IK 01


228S-5C1I-120GE/830, W Luminaire suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Rounded Size: 1587 x 60 x 65 mm Type of installation: Suspended Distribution: Direct-indirect Optics type: Microprisma Protection class: I Voltage: 220-240V

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	10.3 W	CRI	80
Total flux	940 lm	LOR	100%
Luminous efficacy	91 lm/W	ULOR	2%
		Total power	10.3 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	10.3 W	CRI	80
Total flux	940 lm	LOR	100%
Luminous efficacy	91 lm/W	ULOR	2%
		Total power	10.3 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.3 W	CRI	80
Total flux	940 lm	LOR	100%
Luminous efficacy	91 lm/W	ULOR	2%
		Total power	10.3 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.3 W	CRI	80
Total flux	940 lm	LOR	100%
Luminous efficacy	91 lm/W	ULOR	2%
		Total power	10.3 W

Mounting mode

Pendant

Shape and measurements

Length: 15.35 in
Width: 2.36 in
Height: 2.56 in

Adjustability

Fixed

Electric

System power: 41.2 W
Appliance Class: I

Protection

IP: 20
IK: 01