
Product data sheet

48 CAMINO LED OUTDOOR LIGHT FITTING VARIO
48 L50ABX VARIO SL (48001 0563)
SCHUCH



LED outdoor light fitting, CAMINO, 9 W, 35 W, 1160 lm, 5000 lm, 129 lm/W, 143 lm/W, Class II, IP66, asymmetrical extremely wide beam, 4000 K, CRI≥ 70, Ta -40 °C/+25 °C, L90>100000 h (@ Ta max), Pane Safety glass clear, Housing Die-cast aluminium, Colour as required, variable and almost stepless adjustable luminous flux (Attention: only min, max values listed above). LED outdoor light fitting of the GreenLine series with outstanding sustainable product design with variably adjustable luminous flux. Consisting of powder-coated die-cast aluminium housing, two-part. Upper part with ECG, LED modules, optics, switch for setting the luminous flux and frameless tempered safety glass pane, hinged and detachable from the lower part. Lower part with integrated pole mounting system, adjustable inclination, cable entry, strain relief and integrated pressure compensation system (dirt-resistant). Electro kit carrying all electrical components, completely removable by unplugging isolating plug connection. Zhaga LED modules with highly efficient optics, direct beam, Multi-Layer Technology. ECG with high surge protection, overload and short circuit protection. Universal die-cast aluminium pole mounting system for pole-top Ø 60/76mm and side-entry mounting Ø 42/60mm. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 610,00 mm, Width/Diameter 251,00 mm, Height 155,00 mm, Net weight 7,50 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35 W	CRI	70
Total flux	5000 lm	LOR	100%
Luminous efficacy	143 lm/W	ULOR	7%
		Total power	35 W

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 24.02 in
Width: 9.88 in
Height: 6.10 in

Adjustability

Fixed

Electric

System power: 35 W
Appliance Class: I

Protection

IP: 66
IK: 09
Designation labels: CE, ENEC