Product data sheet

PRIMA 1.4FT TRS PC 3200/840 DALI 1F
105122
TREVOS



resistant to dust, humidity and spraying water, the light fitting is suitable for both indoor and outdoor roofed industrial spaces; variable suspension spacing ranging from 700 - 960 mm; enable the light to be installed onto suspension fittings left over from previous lighting; optimal mounting height: 3 to 8 m; digitally dimmable DALI driver (AC/DC); Body: clear PC (high mechanical resistance, UV stability); Diffuser: clear PC (high mechanical resistance, UV stability); Reflector: steel sheet, white (RAL 9003), modified for indirect lighting; Clips: polyamide + 15 % fibreglass; Sealing: polyurethane (PUR), foam-filled base groove; Connection: screwless five-pole terminal block, 5-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand); Power: 20,1 W; Luminaire flux: 3060 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK10; Ambient temperature: -25|50 °C; Weight: 1,9 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20.1 W	CRI	80
Total flux	3260 lm	LOR	100%
Luminous efficacy	162 lm/W	ULOR	4%
		Total power	20.1 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 46.26 in
Width: 3.86 in
Height: 3.31 in

Adjustability

Fixed

Design

Material impression: Plastic
Color of housing: White
Designer: TREVOS

Electric

System power: 20.1 W
Ballast: ECG
Controller: DALI
Appliance Class: I

Protection

IP: 66
IK: 10
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...122°F