


Product data sheet

SKYGARDEN 2 ECO NRO
F6421030
FLOS



Suspension luminaire providing diffused lighting. Hemispherical, cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy. Upper cable gland and blocking ring nut in black injection-molded PC. Shaped, adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lamp-holder and fixing support in PPS. Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment. Gray, injection-molded PC rose, painted the same color as the body. 4000 mm steel wire (1.5 mm diameter). FEP/SIL UV-stabilized transparent power cord length 4000 mm. Net weight 24 kg.

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	42 W	Socket	Gx24Q-4
Lamp flux	3200 lm	LOR	54%
Luminous efficacy	41 lm/W	Total flux	1720 lm
CCT	3000 K	Total power	42 W
CRI	84		

Mounting mode

Pendant

Shape and measurements

Length: 35.76 in
Width: 35.76 in
Height: 17.69 in

Adjustability

Fixed

Electric

System power: 42 W
Appliance Class: I

Protection

IP: 20