Product data sheet

LUCAS IV (1-ARMED) 9.854.2036.15

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire, Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp			
Nominal lamp power	50 W		
Lamp flux	3500 lm		
Luminous efficacy	47 lm/W		
CCT	2000 K		
CRI	25		

LOR	84%
Total flux	2932 lm
Total power	62 W



1 x High pressure sodium vapour lamp				
Nominal lamp power	70 W	LOR	84%	
Lamp flux	5600 lm	Total flux	4691 lm	
Luminous efficacy	57 lm/W	Total power	83 W	
CCT	2000 K			
CRI	25			

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in Diameter: 22.44 in Electric

System power: 62-83 W

Protection

IP: 55