

Product data sheet

PRO-VISION MINI, 12LEDS OPTIEK 4


41340X3X

PROLUMIA




Light Source: Lumileds / Samsung / Osram Color temperature: 3000K / 4000K Color rendering index: Ra ≥ 70 Operating temperature: -30°C ~ +50°C Rated life hours: L90 > 100.000 hours 300-500mA LED driver (included): Philips Xitanium FP programmable / 1-10V / Dali Input: 220-240V AC 50/60Hz Power factor: > 0,95

Light output 1




1 x LED

Nominal lamp power	16.2 W	LOR	100%
Lamp flux	2000 lm	Total flux	2000 lm
Luminous efficacy	123 lm/W	Total power	16.2 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	13.8 W	LOR	100%
Lamp flux	1800 lm	Total flux	1800 lm
Luminous efficacy	130 lm/W	Total power	13.8 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	15.3 W	LOR	100%
Lamp flux	2000 lm	Total flux	2000 lm
Luminous efficacy	131 lm/W	Total power	15.3 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	14.6 W	LOR	100%
Lamp flux	1800 lm	Total flux	1800 lm
Luminous efficacy	123 lm/W	Total power	14.6 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	12.3 W	LOR	100%
Lamp flux	1600 lm	Total flux	1600 lm
Luminous efficacy	130 lm/W	Total power	12.3 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	13 W	LOR	100%
Lamp flux	1600 lm	Total flux	1600 lm
Luminous efficacy	123 lm/W	Total power	13 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	10.7 W	LOR	100%
Lamp flux	1400 lm	Total flux	1400 lm
Luminous efficacy	131 lm/W	Total power	10.7 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	11.3 W	LOR	100%
Lamp flux	1400 lm	Total flux	1400 lm
Luminous efficacy	124 lm/W	Total power	11.3 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted, Pole top mounted

Shape and measurements

Length: 23.62 in

Width: 12.40 in

Height: 5.31 in

Electric

System power: 10.7-16.2 W

Appliance Class: 0

Protection

IP: 66

IK: 08

Designation labels: CE, ENEC