

Product data sheet

VARIOPLAST I
672181.002.07
RZB




IP
00

IK
08

Item Number: 672181.002.07 Series: Varioplast I Type of Protection: IP 55 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Mounting support body plastic (polycarbonate), cover plastic, opal (polycarbonate). Single battery system with integrated self-test and feedback through Dali bus only to the RZB 985405 monitoring system, can optionally be connected in non-maintained power mode (B) or maintained power mode (D). Lamps (LED) included in delivery. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 320, B 186, H 80mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 3h Emergency Lighting System: DALI-Sibe Safety Marks: Ball impact proof in accordance with DIN 18032-03 Impact Protection: IK08 (5 Joule) Luminaire flux LED: 780lm System power: 8,4W Beam Angle: 121°/108° Unified Glare Ratio: 21,3 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.4 W	CRI	80
Total flux	780 lm	LOR	100%
Luminous efficacy	93 lm/W	ULOR	6%
		Total power	8.4 W

Mounting mode

Wall mounted

Shape and measurements

Length: 7.32 in
Width: 12.60 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 8.4 W

Protection

IP: 00
IK: 08