# Product data sheet

MIMO 2 LED 1510MM 4650LM IP66 830 (30W)
100802
LENA LIGHTING



100802 MIMO 2 LED 1510mm 4650lm IP66 830 (30W) MIMO 2 LED represents the new generation of hermetic LED luminaires with very high IP66 tightness. The luminaire uses modern concepts to improve light distribution and temperature balance. Its design involved both proven solutions that affect high efficiency and durability, as well as efficient LED panels offering the best lighting level required and energy savings of up to 66%. The multilayer shade has been made of UV-resistant polycarbonate. Branded LED diodes and new LED modules have influence on a very high luminous efficacy: 150 lm/W.

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 32.7 W | CRI | 80 |
| Total flux | 4650 lm | LOR | 100% |
| Luminous efficacy | 142 lm/W | Total power | 32.7 W |

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 59.45 in
Width: 1.77 in
Height: 1.89 in

### Adjustability

Fixed

### Design

Material impression: Matt
Color of housing: White

### Electric

System power: 32.7 W
Ballast: ECG
Appliance Class: II

### Protection

IP: 66
IK: 06
Designation labels: CE

### Other operating numbers

Ambient temperature range: -4...95°F