

# Product data sheet


NADJA VII (1-ARMED)  
9.876.2036.85  
LEIPZIGER LEUCHTEN



IP  
55

Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711  
Luminaires generally compensatet


## Light output 1



### 1 x High pressure sodium vapour lamp

|                    |         |
|--------------------|---------|
| Nominal lamp power | 50 W    |
| Lamp flux          | 3500 lm |
| Luminous efficacy  | 44 lm/W |
| CCT                | 2000 K  |
| CRI                | 25      |

|             |         |
|-------------|---------|
| LOR         | 78%     |
| Total flux  | 2737 lm |
| Total power | 62 W    |



### 1 x High pressure sodium vapour lamp

|                    |         |
|--------------------|---------|
| Nominal lamp power | 70 W    |
| Lamp flux          | 5600 lm |
| Luminous efficacy  | 53 lm/W |
| CCT                | 2000 K  |
| CRI                | 25      |

|             |         |
|-------------|---------|
| LOR         | 78%     |
| Total flux  | 4379 lm |
| Total power | 83 W    |

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 16.54 in

Diameter: 16.54 in

## Electric

System power: 62-83 W

## Protection

IP: 55