


# Product data sheet

LINA45 45-200K-35GGM3/830, W  
45-200K-35GGM3/830  
HALLA




45-200K-35GGM3/830, W Luminaire surface Material of luminaire: Colour of luminaire: Shape of luminaire: Linear Size: 1969 x 47 x 59 mm  
Type of installation: Surface Distribution: Direct Optics type: Opal diffuser Protection class: I Voltage: 220-240V

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	180 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	1.5 W

## Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	43.8 W	CRI	80
Total flux	3940 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	43.8 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 77.32 in

Width: 1.85 in

Height: 2.32 in

## Adjustability

Fixed

## Electric

System power: 45.3 W

Appliance Class: I

## Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Protection

IP: 20

IK: 01